



(43) International Publication Date
28 April 2005 (28.04.2005)

(10) International Publication Number
WO 2005/037580 A1

PCT

- (51) **International Patent Classification⁷:** **B60G 17/015**, 17/056, 21/06, 21/067, 21/073, 21/08, 23/00, F16F 9/50

(21) **International Application Number:**
PCT/AU2004/001427

(22) **International Filing Date:** 15 October 2004 (15.10.2004)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
2003905717 17 October 2003 (17.10.2003) AU

(71) **Applicant (for all designated States except US):** **ACTIVE AIR SUSPENSIONS LIMITED** [AU/AU]; Unit 9/213 Balcatta Road, Balcatta, Western Australia 6021 (AU).

(72) **Inventor; and**

(75) **Inventor/Applicant (for US only):** **FIELDER, Nicholas, Albert, William** [AU/AU]; 1st Floor, 288 Victoria Road, Malaga, Western Australia 6090 (AU).

(74) **Agent:** **WRAY & ASSOCIATES**; Level 4, The Quadrant, 1 William Street, Perth, Western Australia 6000 (AU).

(81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:
— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VEHICLE SUSPENSION CONTROL



(57) Abstract: A vehicle suspension control for a vehicle having each wheel (11) supported from the chassis of the vehicle through a fluid operated extension element (13, 19), the control comprising a controller (27), a plurality of sensors (21, 23, 25, 27, 30, 32), a fluid flow controller (29), a first sensor (21) adapted to sense the relative position between the wheel (11) and the chassis and provide a first output to the controller, a second sensor (23) adapted to sense the pressure of the fluid in each extension element (13, 19) and provide a second output to the controller (27) adapted to receive the output from each of the sensors (21, 23) at each wheel, process the outputs and provide a wheel output to the fluid flow controller (29) for each wheel, the force applied by the extension elements (13, 19) between the chassis and wheels will maintain the attitude of the chassis substantially constant relative to a plane.